



### BLOOD PRESSURE MONITORS

- LIGHTWEIGHT, COMPACT DESIGNS
- EASY TO READ DISPLAYS
- AUTOMATIC POWER OFF FUNCTIONS

Model #	Description
A 6000	Standard Digital BP with Manual Inflation (UA-702)
B 6005	Standard Digital BP with Manual Inflation & Large Display (UA-711)
C 6010	Auto Inflate & Deflate Digital BP with Large LCD (UA-731)

	Model #6000	Model #6005	Model #6010
Display	Digital	Digital	Digital
Measurement Range (Pressure)	20 - 280mmHg	20 - 280mmHg	20 - 280mmHg
Measurement Range (Pulse)	40 - 200 pulse/minute	40 - 200 pulse/minute	40 - 200 pulse/minute
Accuracy Range (Pressure)	+ 3mmHg or 2% whichever greater	+ 3mmHg or 2% whichever greater	+ 3mmHg or 2% whichever greater
Accuracy Range (Pulse)	+ 5%	+ 5%	+ 5%
Pressurization	Manual or by Rubber bulb	Manual or by Rubber bulb	Automatic
Depressurization	Automatic constant-air-pressure release exhaust valve system	Automatic constant-air-pressure release exhaust valve system	Automatic constant speed exhaust valve
Deflation	Hand held push button	Hand held push button	Automatic
Power Supply	4 Type AAA batteries (SUM-4/R03)	4 Type AAA batteries (SUM-4/R03)	4 Type AAA batteries (SUM-4/R03)
Battery Life (Approximate)	6 months with three measurements daily (3 mins)	6 months with three measurements daily (3 mins)	6 months with three measurements daily (3 mins)
Operating Environment	+ 10°C ~ + 40°C (+ 50°F ~ 104°F), less than 85% RH	+ 10°C ~ + 40°C (+ 50°F ~ 104°F), less than 85% RH	+ 10°C ~ + 40°C (+ 50°F ~ 104°F), less than 85% RH
Storage Environment	- 20°C ~ + 55°C (- 4°F ~ 131°F), less than 95% RH	- 20°C ~ + 55°C (- 4°F ~ 131°F), less than 95% RH	- 20°C ~ + 55°C (- 4°F ~ 131°F), less than 95% RH
Weight (Approximate)	.26 lb	.42 lb	.86 lb
Dimensions (HxWxD)	1.4" x 5.7" x 2.8"	1.4" x 6.4" x 3.3"	1.7" x 7.5" x 3.5"

LIFESTYLE

